

## SFI Smart Film Products

Item	Extra Clear Film Lamination	PDLC film Adhesive	PDLC film Lamination	Automotive Film Adhesive; Lamination
<b>Technology</b>	NCAP PDLC	PDLC	PDLC	PDLC
<b>Width</b>	1000mm	1500mm	1800mm	1200mm
<b>Length</b>	Length – 20m	Length – unlimited	Length – unlimited	Length – unlimited
<b>expose to sun</b>	No	No	No	Yes
<b>Voltage</b>	100-120v	60v	60v	36v
<b>Colors</b>	white	white, light grey, dark grey	white, light grey, dark grey	white, grey
<b>Film thickness</b>	400µm	400µm	400µm	120µm
<b>Adhesive Method</b>		Dry Stick		Wet Stick
<b>Format</b>	Roll only	Roll, Cut to Size	Roll, Cut to Size	Roll, Cut to Size
<b>LOGISTIC</b>				
<b>Lead time</b>	3 weeks	2 weeks	2 weeks	3 weeks
<b>Box size</b>	45 X 45 X 120cm	44 X 44 X 170cm	44 X 44 X 170cm	40 X 40 X 140cm
<b>Time in Market</b>	20+ years	8 years	8 years	4 years
<b>Comment</b>	No 4h daily shut off	No 4h daily shut off	No 4h daily shut off	No 4h daily shut off
<b>Warranty</b>	10 years	2 years	2 years	2 years

# SFI PDLC Detailed Specification

Item	Power	Extra Clear Film Lamination	PDLC film Adhesive	PDLC film Lamination	Automotive Film Adhesive; Lamination
<b>OPTICAL</b>					
<b>VLT</b>	ON	>90%	>70%	>80%	>80%
	OFF	<5%	<5%	<5%	<5%
<b>HAZE</b>	ON	4%	<7%	<7%	<7%
	OFF	>95%	>95%	>95%	>95%
<b>VIEWING ANGLE</b>	ON	180 degrees	150 degrees	150 degrees	150 degrees
<b>UV BLOCKING</b>	ON	>98%	>98%	>98%	>50%
	OFF	>98%	>98%	>98%	>98%
<b>INFRARED BLOCKING</b>	ON	30%	30%	30%	30%
	OFF	85%	85%	85%	85%
<b>ELECTRICAL</b>					
<b>Power supply V</b>	ON	100-120 VAC	65 VAC	65 VAC	65 VAC
<b>RESPONSE TIME</b>	ON à OFF	15ms	10ms	10ms	10ms
	OFF à ON	34ms	200ms	200ms	200ms
<b>POWER CONSUMPTION</b>	ON	<5W/M <sup>2</sup>	<5W/M <sup>2</sup>	<5W/M <sup>2</sup>	<5W/M <sup>2</sup>
<b>AMPERE</b>	ON	110 mA/sqm	150 mA/sqm	200 mA/sqm	100 mA/sqm

Item	Power	Extra Clear Film Lamination	PDLC film Adhesive	PDLC film Lamination	Automotive Film Adhesive; Lamination
<b>ENVIRONMENTAL</b>					
<b>OPERATING TEMPERATURE</b>	ON/OFF	-20°C~ 60°C	-30°C~ 70°C	-30°C~ 70°C	-30°C~ 70°C
<b>STORAGE TEMPERATURE</b>	ON/OFF	-40°C~ 70°C	-30°C~ 70°C	-30°C~ 70°C	-30°C~ 70°C
<b>LIFE (INDOORS)</b>	ON/OFF	>20 years	5-10 years	5-10 years	5-10 years
<b>SIZE</b>					
<b>THICKNESS</b>	ON/OFF	0,4 mm	0,4 mm	0.4 mm	0.12 mm
<b>DIMENSION</b>	ON/OFF	width max. 1400 mm, length unlimited	width max. 1500 mm, length unlimited	width max. 1800 mm, length unlimited	width max. 1200 mm, length unlimited
<b>COLOR</b>	ON/OFF	white	white, light grey, dark grey	white, light grey, dark grey	white, dark
<b>LIGHT GREY FILM</b>					
<b>VLT</b>	ON	none	40%	50%	
	OFF	none	<5%	<5%	
<b>DARK GREY FILM</b>					
<b>VLT</b>	ON	none	30%	40%	
	OFF	none	<5%	<5%	